



Commercial Single Softener - Volumetric (CSSV)

Code	Valve	Conn.	Tank		Filling		Flow rate (m ³ /h)	
			Diameter	Height	Quartz	Resin	30	50
			inch	inch	liter	liter	m/h	m/h
CSSV-1	5600	1"	8	17	2	7	0,3	1,0
CSSV-2	5600	1"	8	35	3	15	0,3	1,0
CSSV-3	5600	1"	10	35	4	25	0,5	1,5
CSSV-4	5600	1"	10	54	4	45	0,5	1,5
CSSV-5	5600	1"	13	44	6	55	0,9	2,6
CSSV-6	5600	1"	10	54	4	45	0,5	1,5
CSSV-7	2750	1"	13	44	6	55	0,9	2,6
CSSV-8	2750	1"	13	54	6	70	0,9	2,6
CSSV-9	2750	1"	14	65	9	100	1,0	3,0
CSSV-10	2750	1"	16	65	9	125	1,3	3,9
CSSV-11	2750	1"	18	65	16	175	1,6	4,9
CSSV-12	2750	1"	21	60	16	225	2,2	6,7
CSSV-13	2850	1 1/2"	16	65	9	125	1,3	3,9
CSSV-14	2850	1 1/2"	18	65	16	175	1,6	4,9
CSSV-15	2850	1 1/2"	21	60	16	225	2,2	6,7
CSSV-16	2850	1 1/2"	24	72	22	300	2,9	8,8
CSSV-17	2850	2"	21	60	16	225	2,2	6,7
CSSV-18	2900	2"	24	72	22	300	2,9	8,8
CSSV-19	2900	2"	30	72	31	450	4,6	13,7

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice