



Media Filter (CMF)

Code	Valve	Conn.	Tank		Filling	Flow rate (m ³ /h)		
			Diameter	Height	Anthracite+	10	20	30
			inch	inch	Quartz (L)	m/h	m/h	m/h
CMF-1	5600	1"	8	17	9	0,3	0,6	1,0
CMF-2	5600	1"	8	35	24	0,3	0,6	1,0
CMF-3	5600	1"	10	35	38	0,5	1,0	1,5
CMF-4	5600	1"	10	54	51	0,5	1,0	1,5
CMF-5	5600	1"	13	44	69	0,9	1,7	2,6
CMF-6	2750	1"	10	54	51	0,5	1,0	1,5
CMF-7	2750	1"	13	44	78	0,9	1,7	2,6
CMF-8	2750	1"	14	65	108	1,0	2,0	3,0
CMF-9	2750	1"	16	65	140	1,3	2,6	3,9
CMF-10	2750	1"	18	65	162	1,6	3,3	4,9
CMF-11	2750	1"	21	60	240	2,2	4,5	6,7
CMF-12	2850	1 1/2"	16	65	112	1,3	2,6	3,9
CMF-13	2850	1 1/2"	18	65	162	1,6	3,3	4,9
CMF-14	2850	1 1/2"	21	60	196	2,2	4,5	6,7
CMF-15	2850	1 1/2"	24	72	276	2,9	5,8	8,8
CMF-16	2900	2"	24	72	276	2,9	5,8	8,8
CMF-17	2900	2"	30	72	371	4,6	9,1	13,7
CMF-18	3150	2"	30	72	371	4,6	9,1	13,7
CMF-19	3150	2"	36	72	640	6,6	13,1	19,7
CMF-20	3150	2"	42	72	842	8,9	17,9	26,8
CMF-21	PLC	2"	30	72	413	4,6	9,1	13,7
CMF-22	PLC	2"	36	72	640	6,6	13,1	19,7
CMF-23	PLC	2 1/2"	42	72	920	8,9	17,9	26,8
CMF-24	PLC	2 1/2"	48	72	1.156	11,7	23,3	35,0

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice