



Commercial Tandem Softener Unit (CTSU)

Code	Valve	Conn.	Tank		Filling Material		Flow rate
			Diameter	Height	Quartz	Resin	
			inch	inch	liter	liter	30 m/h
CTSU-1	9000	3/4"	8	35	2	15	0,6
CTSU-2	9000	3/4"	10	35	3	25	1,0
CTSU-3	9000	3/4"	10	54	3	45	1,0
CTSU-4	9000	3/4"	13	44	5	55	1,7
CTSU-5	9000	3/4"	13	54	5	70	1,7
CTSU-6	9000	1"	14	65	8	100	2,0
CTSU-7	9000	1"	16	65	8	125	2,6
CTSU-8	9000	1"	18	65	16	175	3,3
CTSU-9	9500	1 1/2"	16	65	9	125	2,6
CTSU-10	9500	1 1/2"	18	65	16	175	3,3
CTSU-11	9500	1 1/2"	21	60	16	225	4,5
CTSU-12	9500	1 1/2"	24	71	25	300	5,8
CTSU-13	2900	2"	21	60	16	225	4,5
CTSU-14	2900	2"	24	71	25	300	5,8
CTSU-15	2900	2"	30	72	31	450	9,1
CTSU-16	PLC	2"	24	72	25	300	5,8
CTSU-17	PLC	2"	30	72	31	450	9,1
CTSU-18	PLC	2"	36	72	41	700	13,1
CTSU-19	PLC	2"	42	72	56	900	17,9
CTSU-20	PLC	2"	48	72	78	1.000	23,3
CTSU-21	PLC	2 1/2"	42	72	56	900	17,9
CTSU-22	PLC	2 1/2"	48	72	78	1.000	23,3
CTSU-23	PLC	2 1/2"	48	72	78	1.200	23,3

Operation pressure : 2-8 bar
Operation temperature : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice