



Commercial Single Softener - Timer (CSST)

Code	Valve	Conn.	Tank		Filling	Flow rate (m ³ /h)			Price
			Diameter	Height	Quartz	Resin	30	50	
			inch	inch	liter	liter	m/h	m/h	Euro
CSST-1	5600	1"	8	17	2	7,0	1,0	1,6	230
CSST-2	5600	1"	8	35	3	15,0	1,0	1,6	260
CSST-3	5600	1"	10	35	4	25,0	1,5	2,5	290
CSST-4	5600	1"	10	54	4	45,0	1,5	2,5	330
CSST-5	5600	1"	13	44	6	55,0	2,6	4,3	380
CSST-6	2750	1"	10	54	4	45,0	1,5	2,5	620
CSST-7	2750	1"	13	44	6	55,0	2,6	4,3	660
CSST-8	2750	1"	13	54	6	70,0	2,6	4,3	700
CSST-9	2750	1"	14	65	9	100,0	3,0	5,0	800
CSST-10	2750	1"	16	65	9	125,0	3,9	6,5	870
CSST-11	2750	1"	18	65	16	175,0	4,9	8,2	1.140
CSST-12	2750	1"	21	60	16	225,0	6,7	11,2	1.310
CSST-13	2850	1 1/2"	16	65	9	125,0	3,9	6,5	1.150
CSST-14	2850	1 1/2"	18	65	16	175,0	4,9	8,2	1.400
CSST-15	2850	1 1/2"	21	60	16	225,0	6,7	11,2	1.570
CSST-16	2850	1 1/2"	24	72	22	300,0	8,8	14,6	1.960
CSST-17	2900	2"	21	60	16	225,0	6,7	11,2	1.840
CSST-18	2900	2"	24	72	22	300,0	8,8	14,6	2.230
CSST-19	2900	2"	30	72	31	450,0	13,7	22,8	2.800

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice