



Commercial Tandem Softener Unit (CTSU)

Code	Valve	Conn.	Tank		Filling	Flow rate (m ³ /h)		Price
			Diameter	Height	Quartz	Resin	30	
			inch	inch	liter	liter	m/h	
CTSU-1	9000	3/4"	8	35	2	15	0,6	740
CTSU-2	9000	3/4"	10	35	3	25	1,0	800
CTSU-3	9000	3/4"	10	54	3	45	1,0	880
CTSU-4	9000	3/4"	13	44	5	55	1,7	980
CTSU-5	9000	3/4"	13	54	5	70	1,7	1.040
CTSU-6	9000	1"	14	65	8	100	2,0	1.250
CTSU-7	9000	1"	16	65	8	125	2,6	1.380
CTSU-8	9000	1"	18	65	16	175	3,3	1.860
CTSU-9	9500	1 1/2"	16	65	9	125	2,6	2.830
CTSU-10	9500	1 1/2"	18	65	16	175	3,3	3.190
CTSU-11	9500	1 1/2"	21	60	16	225	4,5	3.530
CTSU-12	9500	1 1/2"	24	71	25	300	5,8	4.280
CTSU-13	2900	2"	21	60	16	225	4,5	4.500
CTSU-14	2900	2"	24	71	25	300	5,8	5.250
CTSU-15	2900	2"	30	72	31	450	9,1	6.340
CTSU-16	PLC	2"	24	72	25	300	5,8	6.820
CTSU-17	PLC	2"	30	72	31	450	9,1	6.820
CTSU-18	PLC	2"	36	72	41	700	13,1	8.310
CTSU-19	PLC	2"	42	72	56	900	17,9	11.060
CTSU-20	PLC	2"	48	72	78	1.000	23,3	11.750
CTSU-21	PLC	2 1/2"	42	72	56	900	17,9	11.250
CTSU-22	PLC	2 1/2"	48	72	78	1.000	23,3	11.970
CTSU-23	PLC	2 1/2"	48	72	78	1.200	23,3	12.600

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice