



Activated Carbon Filter (CAF)''

Code	Valve	Conn.	Tank		Filling	Flow rate (m ³ /h)			Price
			Diameter	Height	A. Carbon+	euro	20	30	
			inch	inch	Quartz (L)		m/h	m/h	euro
CAF-1	5600	1"	8	17	8	0	0,6	1,0	170
CAF-2	5600	1"	8	35	18	0	0,6	1,0	190
CAF-3	5600	1"	10	35	30	1	1,0	1,5	220
CAF-4	5600	1"	10	54	50	1	1,0	1,5	250
CAF-5	5600	1"	13	54	58	1	1,7	2,6	290
CAF-6	2750	1"	10	54	50	1	1,0	1,5	520
CAF-7	2750	1"	13	44	78	1	1,7	2,6	560
CAF-8	2750	1"	13	54	0	1	1,7	2,6	590
CAF-9	2750	1"	14	65	109	1	2,0	3,0	660
CAF-10	2750	1"	16	65	131	1	2,6	3,9	740
CAF-11	2750	1"	18	65	192	2	3,3	4,9	900
CAF-12	2750	1"	21	60	256	2	4,5	6,7	1.040
CAF-13	2850	1 1/2"	16	65	192	1	2,6	3,9	970
CAF-14	2850	1 1/2"	18	65	56	2	3,3	4,9	1.120
CAF-15	2850	1 1/2"	21	60	297	2	4,5	6,7	1.260
CAF-16	2850	1 1/2"	24	72	513	3	5,8	8,8	1.550
CAF-17	2900	2"	24	72	297	3	5,8	8,8	1.800
CAF-18	2900	2"	30	72	513	5	9,1	13,7	2.300
CAF-19	3150	2"	30	72	513	5	9,1	13,7	2.920
CAF-20	3150	2"	36	72	644	7	13,1	19,7	3.440
CAF-21	3150	2"	42	72	825	9	17,9	26,8	4.700
CAF-22	PLC	2"	30	72	313	5	9,1	13,7	2.970
CAF-23	PLC	2"	36	72	444	7	13,1	19,7	3.500
CAF-24	PLC	2 1/2"	42	72	656	9	17,9	26,8	5.040

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice