



Commercial Single Softener - Volumetric (CSSV)

Code	Valve	Conn.	Tank		Filling	Flow rate (m ³ /h)			Price
			Diameter	Height	Quartz	Resin	30	50	
			inch	inch	liter	liter	m/h	m/h	Euro
CSSV-1	5600	1"	8	17	2	7,0	0,3	1,0	290
CSSV-2	5600	1"	8	35	3	15,0	0,3	1,0	320
CSSV-3	5600	1"	10	35	4	25,0	0,5	1,5	350
CSSV-4	5600	1"	10	54	4	45,0	0,5	1,5	390
CSSV-5	5600	1"	13	44	6	55,0	0,9	2,6	440
CSSV-6	5600	1"	10	54	4	45,0	0,5	1,5	760
CSSV-7	2750	1"	13	44	6	55,0	0,9	2,6	810
CSSV-8	2750	1"	13	54	6	70,0	0,9	2,6	840
CSSV-9	2750	1"	14	65	9	100,0	1,0	3,0	940
CSSV-10	2750	1"	16	65	9	125,0	1,3	3,9	1.010
CSSV-11	2750	1"	18	65	16	175,0	1,6	4,9	1.280
CSSV-12	2750	1"	21	60	16	225,0	2,2	6,7	1.450
CSSV-13	2850	1 1/2"	16	65	9	125,0	1,3	3,9	1.630
CSSV-14	2850	1 1/2"	18	65	16	175,0	1,6	4,9	1.880
CSSV-15	2850	1 1/2"	21	60	16	225,0	2,2	6,7	2.050
CSSV-16	2850	1 1/2"	24	72	22	300,0	2,9	8,8	2.440
CSSV-17	2850	2"	21	60	16	225,0	2,2	6,7	2.340
CSSV-18	2900	2"	24	72	22	300,0	2,9	8,8	2.730
CSSV-19	2900	2"	30	72	31	450,0	4,6	13,7	3.300

Operation pressure : 2-8 bar
Operation temp. : 4-40 °C
Pressure loss : 1 bar
Power supply : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice