



### Commercial Single Softener - Timer (CSST)

Code	Valve	Conn.	Tank		Filling		Flow rate (m <sup>3</sup> /h)	
			Diameter	Height	Quartz	Resin	30	50
			inch	inch	liter	liter	m/h	m/h
<b>CSST-1</b>	<b>5600</b>	1"	8	17	2	7	1,0	1,6
<b>CSST-2</b>	<b>5600</b>	1"	8	35	3	15	1,0	1,6
<b>CSST-3</b>	<b>5600</b>	1"	10	35	4	25	1,5	2,5
<b>CSST-4</b>	<b>5600</b>	1"	10	54	4	45	1,5	2,5
<b>CSST-5</b>	<b>5600</b>	1"	13	44	6	55	2,6	4,3
CSST-6	2750	1"	10	54	4	45	1,5	2,5
CSST-7	2750	1"	13	44	6	55	2,6	4,3
CSST-8	2750	1"	13	54	6	70	2,6	4,3
CSST-9	2750	1"	14	65	9	100	3,0	5,0
CSST-10	2750	1"	16	65	9	125	3,9	6,5
CSST-11	2750	1"	18	65	16	175	4,9	8,2
CSST-12	2750	1"	21	60	16	225	6,7	11,2
<b>CSST-13</b>	<b>2850</b>	1 1/2"	16	65	9	125	3,9	6,5
<b>CSST-14</b>	<b>2850</b>	1 1/2"	18	65	16	175	4,9	8,2
<b>CSST-15</b>	<b>2850</b>	1 1/2"	21	60	16	225	6,7	11,2
<b>CSST-16</b>	<b>2850</b>	1 1/2"	24	72	22	300	8,8	14,6
CSST-17	2900	2"	21	60	16	225	6,7	11,2
CSST-18	2900	2"	24	72	22	300	8,8	14,6
CSST-19	2900	2"	30	72	31	450	13,7	22,8

**Operation pressure** : 2-8 bar  
**Operation temp.** : 4-40 °C  
**Pressure loss** : 1 bar  
**Power supply** : 220 V / 50 Hz

enki reserves the right to change the specifications referred to in this table at any time, without prior notice